

Product Code: CMA503

Luckinslive 391864117

Description: 45A 2 Gang (Vertical) Double Pole Plate Switch With White Rocker &amp; Neon



### General Information

Plate Dimensions (mm)	86 (W) x 146 (H) x 9.5 (D)
Plate Fixing Centres - Vertical (mm)	120.6
Style	Rounded Profile
Colour	Polar White
Materials	Front Plate: Urea Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	Yes
Operating Voltage (AC)	250
Resistive Load Rating (A)	45
Termination Type	Screw
Terminal Size (mm)	Ø6
Terminal Capacity - Solid (mm <sup>2</sup> )	1 x 16
Double Pole Switch	Yes
Twin Earth Terminals	Yes
Neon Indicator	Yes
Product Marking	On & Off
Minimum Back Box Depth (mm)	35
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	25
Frequency (Hz)	50
Terminal Torque Value (Nm)	2.5
Indicator Colour	Orange

**Standards** BS EN 60669-1

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.