

**General Information**

| | |
|--|---|
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 11 (D) |
| Plate Fixing Centres - Horizontal (mm) | 60.3 |
| Style | Square Edge |
| Colour | Polar White |
| Materials | Front Plate & Fuse Drawer: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass |
| Anti Microbial Certified | Yes |
| Operating Voltage (AC) | 250 |
| Resistive Load Rating (A) | 13 |
| Fuse Fitted Type | Plug Top Cartridge Fuse |
| Termination Type | Screw |
| Terminal Size (mm) | Ø5 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 |
| Switched | No |
| Twin Earth Terminals | Yes |
| Product Marking | Fused |
| Flex Outlet Available | Yes |
| Flex Outlet Location | Bottom of Plate |
| Minimum Back Box Depth (mm) | 25 |
| Ingress Protection | IP20 |
| Operational Temperature (°C) | -5 to +40 |
| Warranty (Years) | 25 |
| Frequency (Hz) | 50 |
| Terminal Torque Value (Nm) | 2 |
| Flex Outlet Dimension (mm) | Ø10 |

Standards BS 1363-4, BS 1362**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.