

3 3 Years
Product Warranty

Mains Dimmable
Dimmable

General Specification

Voltage 220-240Vac
50/60Hz
CRI >80
Power Factor 0.50
L70B50 Lifetime 15,000h
Ambient Temp -20°C to 50°C

Order Code

A5.9D-BC27
A5.9D-ES27
A5.9D-BC40
A5.9D-ES40
A5.9D-BC27
A5.9D-ES27
A5.9D-BC40
A5.9D-ES40
A5.9D-BC65
A5.9D-ES65



A9.5D-BC27
A9.5D-ES27
A9.5D-BC40
A9.5D-ES40
A9.5D-BC65
A9.5D-ES65

A3.4-BC27
A3.4-ES27
A3.4-BC40
A3.4-ES40
A3.4-BC65
A3.4-ES65

A5.9-BC27
A5.9-ES27
A5.9-BC40
A5.9-ES40
A5.9-BC65
A5.9-ES65

A9.5-BC27
A9.5-ES27
A9.5-BC40
A9.5-ES40
A9.5-BC65
A9.5-ES65

Dimensions



GLS

Classic shaped LED GLS

- High efficiency up to 138lm/W
- Save energy by up to 90%
- Replacement for incandescent GLS, candle and golf lamps
- Choices of 2700K/4000K/6500K
- Dimmable options



Ultra-high efficiency

Up to
138 $\frac{\text{lm}}{\text{W}}$



Dimmable GLS

Energy Class: **D** A t G

Order Code	Power	Cap	CCT	Lumen
A5.9D	5.9W	B22 E27	2700K 4000K 6500K	806lm
A9.5D	9.5W	B22 E27	2700K 4000K 6500K	1055lm

Non-Dimmable GLS

Energy Class: **D** A t G

Order Code	Power	Cap	CCT	Lumen
A3.4	3.4W	B22 E27	2700K 4000K 6500K	470lm
A5.9	5.9W	B22 E27	2700K 4000K 6500K	806lm
A9.5	9.5W	B22 E27	2700K 4000K 6500K	1055lm

RF wireless triac dimmer

Order Code	Max Power	Output Current
CYDIMRFT1	2 x 120W (100 Vac) 2 x 288W (240 Vac)	2 x 1.2 A

* See datasheet for recommended number of lamps per dimmer