

- 5** 5 Years
Product Warranty
- 2** 2 Years
On-Site Warranty
- 1000V**
Surge Protection
- DALI, 0-10V & PUSH**
Dimmable Options
- Casambi**
Dimmable Options

Recommended

Emergency Module
UEM ↪ P65Emergency Module
UEM Pro ↪ P62Emergency Kit
Niah ↪ P110Anti-glare diffuser
Diffuser Accessories ↪ P151

General Specification

Voltage	220-240Vac 50/60Hz
CRI	82
SDCM	<3
L80B10 Lifetime	111000h
Power Factor	>0.90
Ambient Temp	-20°C to 50°C
Housing	Iron + Aluminium
Diffuser	Polystyrene TP(a)



Alden III

Anti-glare backlit LED panel
with emergency option

- UGR<17*
- TP(a)-rated diffuser for enhanced fire safety
- DALI, 0-10V and PUSH dimming alternative driver available
- Optional plug-in emergency modules, available in standard, self-test and DALI
- IP44 when ceiling recess-mounted
- Visual comfort flicker-free technology with short term flicker perceptibility (Pst) being measured at 0
- SDCM<3

Plug-in emergency

Visual comfort

UGR<17

Push-wire terminal
block included

Alden III

Order Code	Power	Dimension	CCT	Lumen
ALD330	30W	595x595	3000K 4000K 6500K	3200lm

Alden II

Order Code	Power	Dimension	CCT	Lumen
ALD1206	50W	1195x595	4000K 6500K	5300lm

* UGR<17 for room size of 4h x 2h, UGR<19 for room size of 4h x 8h

Optional Gears

Type	Order Code	Description
Casambi Dimmable driver	DRC42/CSB	Bluetooth & PUSH button dimmable driver
Dimmable driver	DRC30/DA	Configurable DALI, 0-10V & PUSH Dimmable Driver for ALD330
Dimmable driver	DRC40/DA	Configurable DALI, 0-10V & PUSH Dimmable Driver for ALD330, ALD1206
Emergency module	UEM03	Standard UEM, 3W, Li-ion battery
Emergency module	UEM03/SST	Standard & Self-test 2 in 1 UEM, 3W, Li-ion battery
Emergency module	UEM04	Standard UEM Pro, 4W, Li-ion battery, 2 x 3-core cable terminals
Emergency module	UEM04/SST	Standard & Self-test 2 in 1 UEM Pro, 4W, Li-ion battery, 2 x 3-core cable terminals
DALI-2 emergency module	UEM04/DA	DALI-2 UEM Pro, 4W, Li-ion battery, 2 x 3-core cable terminals
Emergency kit	EMPAD02	Standard emergency kit
Emergency kit	EMPAD02/SST	Standard & Self-test 2 in 1 emergency kit

Accessories

Type	Order Code	Description
Surface-mount frame	SMT0606	595x595mm surface-mount frame, white
Surface-mount frame	SMT1206	595x1195mm surface-mount frame, white
SAS/Burgess Clips	SAS0606	Clips for SAS150, SAS120 & Burgess ceilings
Sky light recessed frame	SRF0606	595x595mm sky light recessed frame, white
Suspension kits	SUS04	Maximum 1.0m drop
Suspension kits	SUS04/25	Maximum 2.5m drop
Recessed-mount frame	REC0606	595x595mm recessed-mount frame, white
Recessed-mount frame	REC1206	1195x595mm recessed-mount frame, white
Diffuser	ALDAG-0606	595x595mm anti-glare diffuser
Diffuser	ALDAG-1206	1195x595mm anti-glare diffuser

Order Code

ALD330-W30
ALD330-W40
ALD330-W65

ALD1206-W40
ALD1206-W65

Dimensions

