


5 5 Years
Product Warranty

3 3 Years
On-Site Warranty

Recommended



Lulu
(Mounting height ≤ 6m)
↪ P21



Remote Control
RMT-UNI



DD EME II ↪ P67



Lamp Holder
DDLAMPHLD

General Specification

Voltage 220-240Vac
50/60Hz
CRI >80
Power Factor >0.80
L70B50 Lifetime 30,000h
Ambient Temp -20°C to 50°C

DD II Mini

Upgrade
Apr. 2025

Retrofit replacement for popular
CFL DD lamps

- High efficiency up to 145lm/W
- Switchable wattage and CCT (2700/4000/6500K)
- Optional plug-in microwave corridor sensor compatible with Uni-Remote
- Optional plug-in emergency modules, available in standard, self-test and DALI
- Save energy by up to 65%
- Replacement for 16W fluorescent DD lamps used with magnetic ballast

Plug-in emergency

Plug-in corridor sensor

Wattage switching

CCT switching

Flicker-free

Modular design

EM driver isolation*

* LED Driver and LED light source are switched off in emergency mode.

Uni-Remote Compatible



Up to
145 lm/w

Order Code	Default Power	Alternative Power	Cap	Beam Angle	CCT	Lumen	Energy Class
DD212	-	6W	GR8 GR10q	120°	Switchable*	780lm (2700K) 830lm (4000K) 820lm (6500K)	
	-	8W				1060lm (2700K) 1150lm (4000K) 1120lm (6500K)	
	-	10W				1330lm (2700K) 1450lm (4000K) 1390lm (6500K)	
	12W	-				1550lm (2700K) 1720lm (4000K) 1630lm (6500K)	

* When CCT switchable, colour temperature switches between 2700K, 4000K & 6500K

Optional Gears

Type	Order Code	Description
Emergency module	EMDD202	Standard emergency module, LiFePO4 battery
Emergency module	EMDD202/SST	Standard & Self-test 2 in 1 emergency module, LiFePO4 battery
DALI-2 Emergency module	EMDD202/DA	DALI-2 emergency module, LiFePO4 battery
Microwave Sensor	LUL-M/D	ON/OFF, Dimming (PWM)

Accessories

Type	Order Code	Description
Lamp holder	DDLAMPHLD	GR10q lamp holder
Remote Control	RMT-UNI	Universal Remote Control for LUL-M/D

Patent

Order Code
DD212/2P-SCT
DD212/4P-SCT

Dimensions

