

Upgrade
May. 2025

Mulu

Standard IP65 LED emergency exit sign bulkhead

Battery warranty



Temp. Control



- All legends included
- Maintained and non-maintained option
- 20mm Conduit entry
- IP65 and IK10 (vandal resistant) for internal & external uses
- Dual entry push-wire terminal block for easy loop-in loop-out wiring
- BESA box fitting points



▲ Rotatable arrow sign



Standard With Temp. Control

Order Code	Input Power (max)	Emergency Output Power	CCT	Lumen
MUL0105	5W	1.5W	6500K	80lm
MUL0105-BLK	5W	1.5W	6500K	60lm

Self-test (Only)

Order Code	Input Power (max)	Emergency Output Power	CCT	Lumen
MUL0105/ST	5W	1W	6500K	80lm
MUL0105-BLK/ST	5W	1W	6500K	60lm

Battery

Order Code	Type	Capacity	Voltage
BATC18LFP1 (for standard)	LiFePO4	1800mAh	3.2V
BAT18LFP1 (for self-test)	LiFePO4	1800mAh	3.2V


- 5** 5 Years Product Warranty
- 2** 2 Years On-Site Warranty
- 1000V** Surge Protection



Black finish

General Specification

Input Voltage	220-240Vac
Conversion Time	50/60Hz
Input Current (max)	40mA
Lifetime	50,000h
Emergency Operation Time	<1s
Charging Time	3h
Ambient Temp	24h
Housing	0°C to 50°C
Diffuser	ABS
	Polycarbonate

P125
Spacing table

Order Code

MUL0105
MUL0105-BLK
MUL0105/ST
MUL0105-BLK/ST

Dimensions

