

- 5** 5 Years Product Warranty
- 2** 2 Years On-Site Warranty
- 1000V** Surge Protection



Mounting on trunking  
(Mounting brackets included)

### General Specification

Input Voltage	220-240Vac
Frequency	50/60Hz
Input Current (max)	35mA
CRI	80
Lifetime	50,000h
Emergency Conversion Time	<1s
Emergency Operation Time	3h
Charging Time	24h
Ambient Temp	0°C to 50°C
Maximum Case Temp	75°C
Housing	Polycarbonate



### Order Code

ORD03-WHT



ORD03-WHT/ST

ORD03-BLK/ST

ORD06-WHT/ST

ORD06-BLK/ST

### Dimensions



# Orda II

Upgrade  
Jun. 2025

Standard high-Efficient twin spot LED emergency light

- Ceiling-mount option and accessories included
- Fully adjustable twin heads allow best light coverage
- Non-maintained
- IP65, IK10

**5** YEAR Battery warranty

Temp. Control



Standard Emergency

### Standard With Temp. Control

Order Code	Input Power	Emergency Output Power	Beam Angle	Finish	CCT	Lumen
ORD03	3.5W	3W	110°	White	6500K	370lm 330lm

### Self-test (Only)

Order Code	Input Power	Emergency Output Power	Beam Angle	Finish	CCT	Lumen
ORD03/ST	3.5W	3W	110°	White Black	6500K	370lm 330lm
ORD06/ST	6.5W	6W	110°	White Black	6500K	650lm 550lm

### Battery

Order Code	Type	Capacity	Voltage
BATC20LFP2/L	LiFePO4	2000mAh	6.4V